

Rotators

Rotator, fixed speed, SB2

- Fully adjustable mixing angle
- Constant speed of 20rpm
- Choice of tube holders to hold a number of different sized tubes
- Simple on/off control switch
- Spillage tray

The SB2 gives gentle but effective mixing, ideal for keeping biological samples in suspension e.g. blood

The rotator can be used in incubators up to 60°C and in cold rooms down to 4°C.

The rotator has a constant speed of 20rpm and the angle of rotation is fully adjustable, from horizontal for minimal mixing to vertical for full end-over-end mixing.

An integral tray catches any spillage from the rotating tubes. A choice of six tube holders are available to fulfil most applications. It is possible to use two tube holders simultaneously with our dual holder accessory.

Technical Specification

SB2	
Speed range	Fixed to 20rpm
Dimensions, mm (w x d x h)	200 x 270 x 230
Net weight, kg	3.2
Electrical supply	230V, 50Hz, 50W
IP Rating	31

Ordering Information

Model	Description
SB2	Rotator, fixed speed

Tube holders

- Choice of six types
- Quick and easy loading and removal of tubes
- End-over-end or rolling action

Ordering Information

Model	Description	Tube diameter	Max. no. of tubes
End-over-end action			
SB3/1	Micro tube holder	10 to 11.5 mm	40
SB3/2	Test/blood tube holder	9 to 20mm	20
SB3/3	50ml centrifuge tube holder	25 to 35 mm	12
Rolling action			
SB3/4	Culture tube holder	12mm	63
SB3/5	Culture tube holder	16mm	63
SB3/6	Culture tube holder	26mm	30

Accessories

SB2/DUAL	Multiple tube holder accessory
SB3/1/PC	Spare clips for SB3/1 holder



SB2 & SB3/2



SB3/2

SB3/4

SB3/3

SB3/1